

Dimensions and basic data	Norm	Planks	Wide planks	Tiles
Width:	ISO24342	178	mm 228	mm 610
Length:	ISO24342	1219	mm 1219	mm 305
Number of panels per pack:	-	10	pc 8	pc 12
m <sup>2</sup> per pack:	-	2,17	m <sup>2</sup> 2,22	m <sup>2</sup> 2,23
Weight per pack:	ISO23997	45	pak 45	pak 60
Total thickness:	ISO24346	17,4	kg 17,4	kg 18,75
Top Layer thickness:	EN429	5	mm 5	mm 5
		(4mm SPC + 1 mm XPE)	(4mm SPC + 1 mm XPE)	(4mm SPC + 1 mm XPE)
		0,55	mm 0,55	mm 0,55
Warranty	Norm	Results		
Usage class:	ISO10582	33		
CE:	EN 14041	DoP BRI001		
Warranty:	Residential use:	10 years		
Technical data	Norm	Results		
Residual indentation:	ISO24343-1	≤ 0,2 mm		
Stain resistance:	EN438-2	OK_Group 1,2 and 3: degree 5		
UV resistance:	ISO 105-B02:1994, Method 3a	> 6		
Fire classification:	EN 13501-1 ISO 9239-1	Bfl-s1		
Dimensional stability:	EN ISO23999 6uur bij 80C	≤ 0,10 %		
Locking strength:	ISO24334	Long side: > 4,5kN/m		
Castor chairs:	EN ISO4918	OK		
Slip resistance:	EN13893 EN 16165	DS R10		
Swelling:	ISO24336	0%		
Thermal resistance (floor + underlay):	EN12667	<0,15R (m <sup>2</sup> K/W)		
Floor heating:		Appropriate for all standard heating systems IN cement flooring. NOT appropriate for heating films.		
Impact sound improvement:	ISO 10140 / ISO717-2	ΔLw18dB		
Dangerous Substances				
Formaldehyde emission:	EN14041 / EN717-1	E1		
TVOC 28 days:	<1000µg/m <sup>3</sup>	<10µg/m <sup>3</sup>		
Emissions in the interior air:	Décret n° 2011-321	A+		
REACH:	-	Brigid® floors are fully REACH compliant		
Plasticizers:	-	DOTP - virgin PVC - 100% orthophtalate free		

Floorify NV reserves the right to make alterations to material and structures when this serves to improve the quality  
Floorify NV, Kruisboommolenstraat 30A 8800 ROESELARE, BELGIUM - Email: hello@Floorify.com -T+32 (0)51 140 180